

W.Nr.1.2312

thickness	22		27		36		46		56		66		76		86		96		106		116		126		136				
	w	l	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc	stock pcs	EUR/pc			
156 x 156			1	11	5	12			2	23	1	26																	
156 X 196			1	13	38	16	26	19	25	24	6	28	7	32	3	37													
156 X 246					2	19	1	24			2	35	2	41															
156 X 296					3	23	1	29	6	35	2	42	2	48															
196 X 196			4	16	26	19	28	24	19	29	14	35	18	41	8	46	2	52											
196 X 246					1	24			2	36	1	43			1	58	1	64											
196 x 296					10	28	4	36	4	44	5	52	4	60	1	68													
196 X 346					1	32			2	52	2	61	1	71	1	80	2	90											
196 X 396			4	32	3	37	1	47	1	59	5	70	3	80	1	91	2	102											
246 x 246			1	25	1	29	2	37	2	46	1	54	1	62			3	80	1	89									
246 X 296			2	30	3	35			2	55	3	65			7	85	1	96	1	106									
246 x 346			3	35	1	41	2	52			7	76	3	88	1	100	4	112	2	124									
246 X 396			3	40			1	59	3	73								2	142										
246 X 446													1	115					2	142									
296 x 296						9	53	7	65	3	78	3	90	3	102	5	115			2	138			1	166				
296 x 346								6	76	1	90			4	119			4	148					1	190				
296 x 396					1	55			6	103	2	120	2	137	1	152	3	169	1	185	1	202	1	202		1	235		
296 x 446					1	62	2	79		1	116	2	122	2	154	1	172	1	190			2	227			2	264		
346 x 346						2	72					2	122	1	139	1	156	1	173			2	206	2	206		1	240	
346 x 396													2	139			3	178			2	214			1	252			
396 x 396																											2	312	
396 X 446									1	152	2	177	1	202			1	251											
396 X 496							1	142	3	169	2	197	2	224	3	251													
446 X 446																						1	337			1	361		
496 X 496																					1	382			1	451	1	485	

* plates are milled in tol. +1,0/+2,0 mm,
 * after cutting are plates stress-relief annealed,